

DxO ONE

PRO QUALITY

CAMERA.
MINIATURIZED.

CONNECTED

Shot with DxO ONE © Muriel Franceschetti

The DxO ONE is a miniaturized, pro-quality camera. Equipped with a 1-inch sensor and a wide-aperture lens, the DxO ONE takes unforgettable photos even in low-light conditions. When directly connected to an iPhone or iPad, the DxO ONE features capabilities on par with those of a professional camera. You can also instantly send high-resolution photos to your friends and family and post your images on social media.

PRICING AND AVAILABILITY

The DxO ONE is available at www.dxo.com, Amazon, and other major retailers for a suggested retail price of **\$499 / £399 / 499 €**.

More information at
www.dxo.com/en/retailers



The world's smallest 1" format sensor camera: Under three inches tall and weighing less than an iPhone.

Lightning connector directly connects to your iPhone or iPad, transforming your device into a high-definition viewfinder whose Retina display provides access to all the controls of a DSLR.

Wi-Fi remote control capability using existing network (LAN) or direct connection.

Standalone mode and Framing Assistant allow you to quickly compose and take photos with one hand.

Instantly share your DxO images from your iPhone to Facebook, Twitter, Instagram, and more.

Intuitive integration with Apple iOS for immediate access to the Photos application and editing tools.

Rechargeable Lithium-ion battery and microSD card ensure that the DxO ONE never impacts your iPhone's talk time or storage.

Integrated online store lets you order DxO ONE accessories from anywhere.

TECHNICAL SPECIFICATIONS

Still resolution	20.2 megapixels (5406 x 3604)	Camera modes	Automatic, sports, portrait, landscape, night, program, aperture priority, speed priority, manual, and selfie
Video resolution	1080p at 30 fps, 720p at 120 fps	Video modes	Full HD, slow motion (x4)
Sensor size	1-inch format (13.2 x 8.8 mm)	Files formats	JPG, .DNG (RAW), .DXO (SuperRAW), .MOV (H.264)
Sensor type	CMOS - BSI	Focus range	20 cm to infinity
Focal length	11.9 mm (equivalent to 32 mm in full-frame)	Autofocus	Contrast detect, using face detection
Lens cover	Integrated, sliding (on/off)	Focus modes	Single-shot, continuous, tap-to-focus, manual focus
Aperture	f/1.8 adjustable down to f/11 (six-blade iris)	Metering modes	Spot, center-weighted, multi-zone
Shutter button	Half-press to autofocus	Zoom	Digital 3x
OLED screen	Settings display, touchscreen	Weight	3.81 oz (108 g)
ISO range	100 to 51200 (Hi2)	Dimensions	2.65 x 1.92 x 1.03 inches (67.5 x 48.85 x 26.25 mm)
Shutter speed	1/20000 to 30 s		
Image stabilization	Electronic (for video)		

Made for: iPhone 7, iPhone 7 Plus, iPhone SE, iPhone 6s Plus, iPhone 6s, iPhone 6 Plus, iPhone 6, iPhone 5s, iPhone 5c, iPhone 5, iPad Pro, iPad Air 2, iPad mini 4, iPad mini 3, iPad Air, iPad mini 2, iPad (4th generation), iOS 9.0 or later, WatchOS 2.0.

Box content: DxO ONE, 8GB microSD card, USB cable, wrist lanyard, soft pouch, DxO Connect (as a free download, Mac/PC), DxO OpticsPro for OS X Photos - DxO ONE Camera only.

Outdoor Shell

TAKE YOUR

DxO ONE EVERYWHERE

Extremely rugged, yet quick and easy to attach, the protective and waterproof Outdoor Shell lets you take the DxO ONE camera where no DSLR or smartphone can go. Combined with the Wi-Fi connectivity of the DxO ONE, it dramatically extends the fields of use of the camera.

PRICING AND AVAILABILITY

The Outdoor Shell is available at www.dxo.com, Amazon and other major retailers for a suggested price of **\$59.99 / £49.99 / 59.90 €**.

More information at www.dxo.com/en/retailers



Splashproof: Suitable for surfing, sailing, snow sports, or just walks in the rain (IP67).

Waterproof for full immersion sports, such as swimming and snorkeling, to depths of 150 ft (45 m).

Ergonomic fit and non-slip (golf ball) texture make the shell ideal for handheld use.

Lanyard attachment point for leashing, including use with non-submersible wrist bands to float the camera and prevent sinking.

Innovative sealed power switching system with integrated switch.

Translucent back doors provide unobstructed view of the OLED display:

- **Submersible Back Door** for underwater activities.
- **Touch Back Door** for activities involving a modest amount of splashing, supports firm swiping and touching through the window membrane to use the controls on the OLED display, without removing the case.

30.5mm optical add-ons, such as close-up adapters, can be mounted by securing them on the built-in thread.

TECHNICAL SPECIFICATIONS

Water resistant to: 150 ft (45 m)
Shockproof to: 6' 7" (2 m) on concrete
Freezeproof to: 14 °F (-10 °C)
Crushproof to: 120 N
Operating thermal range (in air/in water): 14 °F / 122 °F (-10 °C / +50 °C)
Operating altitude/pressure: 9800 ft (3000 m) / 0.3 bar

Materials: Silicon, stainless steel, PC, neodymium, glass, Teflon, aluminium
Weight: Front: 2.54 oz (72 g)
 Submersible Back Door: 0.74 oz (21 g)
 Touch Back Door: 0.7 oz (19,9 g)
 With DxO ONE: 7.23 oz (205 g)
Dimensions: 3.86 x 2.56 x 1.85 inches (98 x 65 x 47 mm)

Box content: Outdoor Shell, Submersible Back Door, Touch Back Door, soft pouch, wrist lanyard, 30.5mm lens cap.



PRICING AND AVAILABILITY

The Stand is available at www.dxo.com, Amazon, and other major retailers for a suggested retail price of **\$24.99 / £19.99 / 24.90 €**.

Stand

The high precision, simple and versatile DxO ONE Stand dramatically extends the use cases for the DxO ONE when stability is required (e.g., group selfies, astrophotography, etc.). It lets you balance your DxO ONE on almost any surface or mount it to a tripod.

Micrometric adjustment clamp firmly secures the camera, which can be removed or re-attached quickly and easily.

Features a standard ¼-20 (ISO 1222) thread nut allowing the stand to be mounted on any standard tripod or monopod.

Dovetail-shaped base is compatible with Mini Arca-Swiss clamps and MeFOTO DayTrip mounts.

Non-slip rubber sole prevents sliding on flat surfaces with 0.5 mm of cushioning when secured on a tripod to help prevent vibration propagation.

Built-in lanyard attachment for leashing to your photographic equipment when not in use.

Materials:	Black anodised aluminium, ABS/PC, brass
Weight:	0.49 oz (13.8 g)
Dimensions:	2.17 x 0.98 x 1.14 inches (55 x 25 x 29 mm)



PRICING AND AVAILABILITY

The Optical Adapter (pack of 3 units) is available at www.dxo.com, Amazon, and other major retailers for a suggested retail price of **\$24.99 / £19.99 / 24.90 €**.

Optical Adapter

Unleash even more creative possibilities by complementing your DxO ONE with standard 30.5mm thread filters, macro lenses, hoods, and the like.

Allows standard ND and creative filters, macro lenses, hoods, etc. to be mounted in front of the lens.

Features an industry-standard 30.5mm thread ring made of black anodized precision aluminum for reliability and durability.

Firmly secures to the DxO ONE front bezel with a snap.

Can also be used as a low-profile shade/hood to help prevent lens flares due to strong sideways light beams.

Materials:	Aluminium and ABS/PC
Weight:	0.11 oz (3 g)
Dimensions:	1.38 x 1.38 x 0.43 inches (35 x 35 x 11 mm)



PRICING AND AVAILABILITY

The Zipped Pouch is available at www.dxo.com, Amazon, and other major retailers for a suggested retail price of **\$19.99 / £15.99 / 19.90 €**.

Zipped Pouch

Protect your DxO ONE while always keeping it at the ready for when creativity strikes.

Attaches to most belts, straps and lanyards to protect your DxO ONE, while keeping it close and ready for action.

Cushioning EVA foam layer protects the camera from most drops and impacts.

Double overlapping VELCRO brand straps quickly and easily secure the pouch to your belt or a strap.

Stainless steel key ring secures the pouch to most keychains or carabiners.

Elastic retainers prevent the camera from falling out while the unzipped shell is open.

Materials:	Scratchproof nylon ballistic CORDURA fabric, velvet
Weight:	1.19 oz (33.6 g)
Dimensions:	3.19 x 2.48 x 1.61 inches (81 x 63 x 41 mm)